



PRODUCT, REEL & PACKAGING SPECIFICATIONS

Film type : **CMT10B441/1630**

Revision nr. : **01**

Product and Reel Specifications

Properties	Unit	Limit values	Tolerances	Method
Thickness	μ	10	± 10 %	ASTM E252 rev. 90
Ultimate tensile TD	kg	26	> 20	
Elongation at break MD	%	120	> 100	ASTM D1709 rev.85
Elongation at break TD	%	600	750	ASTM D1709 rev.85
Net Roll weight	Kg	6.59	± 5 %	-
Core weight	Kg	0.98	± 1%	-
Roll length	m	1630	± 5 %	-
Film width	mm	440	± 5 %	-
Core length	mm	482	± 2 mm	-
Inside core diameter	mm	76	± 2 mm	-
Outside diameter	mm	260	± 5 mm	-
Cling		Inside		

Film warranty for 6 months from production date

Packaging Specifications

	Unit	Feature
Pallet size	mm	800 x 1200
Number of reels per pallet	-	30
Pallet GFN weight	kg	247
Palletization/nr of layers		V-2

<i>Name</i>	Christelle Gilson
<i>Function</i>	Technical Development Manager
<i>Date</i>	01/03/2013

Original print-out including above mentioned approvals is available in the Quality Assurance Department
THE DATA CONTAINED HEREIN ARE PROPRIETARY AND MUST REMAIN
CONFIDENTIAL

