



PRODUCT, REEL & PACKAGING SPECIFICATIONS

Film type : **MHB09B430/0500**

Revision nr. : **02**

Product and Reel Specifications

Properties	Unit	Typical	Limit values	Method
Thickness	µm	8.6	± 10 %	ASTM E252 rev. 90
Tear strength	MD	130	> 80	ASTM D1922 rev. 89
	TD	320	> 280	
Ball Drop	g	155	> 100	ASTM D1709 rev.85
Roll weight	kg	2.17	± 5 %	-
Roll length	m	500	± 5 %	-
Film width	mm	430	± 5 %	-
Core length	mm	480	± 2 mm	-
Inside core diameter	mm	50	± 1 mm	-
Outside diameter	mm	113	± 4 mm	-
Cling	Inside			

Film warranty for 6 months from production date

Packaging Specifications

	Unit	Feature
Pallet size	mm	1200 x 1000
Number of reels per pallet	-	300
Pallet GFN weight	Kg	648
Palletization/nr of layers		V-3

Name	Stéphanie Lahaye
Function	Technical Development Manager
Date	03/02/2011

Original print-out including above mentioned approvals is available in the Quality Assurance Department
THE DATA CONTAINED HEREIN ARE PROPRIETARY AND MUST REMAIN CONFIDENTIAL