



PRODUCT, REEL & PACKAGING SPECIFICATIONS

Film type : **MMT07B440/4200**

Revision nr. : **09**

Product and Reel Specifications

Properties	Unit	Typical	Limit values	Method
Thickness	µm	6.6	± 10 %	ASTM E252 rev. 90
Tear strength	MD	100	> 60	ASTM D1922 rev. 89
	TD	270	> 210	
Ball Drop	g	150	> 80	ASTM D1709 rev.85
Roll weight	kg	12.5	± 5 %	-
Roll length	m	4200	± 5 %	-
Film width	mm	440	± 5 %	-
Core length	mm	482	± 2 mm	-
Inside core diameter	mm	76	± 1 mm	-
Outside diameter	mm	257	± 5 %	-
Cling	Inside			

Film warranty for 6 months from production date

Packaging Specifications

	Unit	Feature
Pallet size	mm	1200 x 1000
Number of reels per pallet	-	36
Pallet GFN weight	kg	450
Palletization/nr of layers		V-2

<i>Name</i>	Christelle Gilson
<i>Function</i>	Market Development Manager
<i>Date</i>	01/09/2011

Original print-out including above mentioned approvals is available in the Quality Assurance Department
THE DATA CONTAINED HEREIN ARE PROPRIETARY AND MUST REMAIN
CONFIDENTIAL