

## PRODUCT, REEL & PACKAGING SPECIFICATIONS

	-	ı	
Film type:	MMT07B390/4200	Revision nr. :	00

## Product and Reel Specifications

Properties	Unit	Typical	Limit values	Method
Thickness	μm	6.6	± 10 %	ASTM E252 rev. 90
Tear strength MD TD	g	100 270	> 60 > 210	ASTM D1922 rev. 89
Ball Drop	g	150	> 80	ASTM D1709 rev.85
Roll weight	kg	11.15	± 5 %	-
Roll length	m	4200	± 5 %	-
Film width	mm	390	± 5 %	-
Core length	mm	442	± 2 mm	-
Inside core diameter	mm	76	± 1 mm	-
Outside diameter	mm	257	±3 %	-
Cling	lr	side		

Film warranty for 6 months from production date

## Packaging Specifications

	Unit	Feature
Pallet size	mm	1000 x 1200
Number of reels per pallet	-	36
Pallet GFN weight	kg	401.4
Palletization/nr of layers		V-2

Name	Christelle Gilson
Function	Market Development Manager
Date	02/12/2012

Original print-out including above mentioned approvals is available in the Quality Assurance Department THE DATA CONTAINED HEREIN ARE PROPRIETARY AND MUST REMAIN CONFIDENTIAL